

## > PRODUCT PLUS

### POWER AND COMPACTNESS COMBINED

SDMO can now supply a 27kVA generating set integrated in a particularly compact enclosure. The K27 is now mounted in an M126 enclosure.



soundproofed version **K27**



soundproofed version **K9**

## THREE-PHASE SPECIFICATIONS

Generating sets		Standard enclosures				Enclosures with double wall base frame			Sound levels 50 Hz			Sound levels 60 Hz
50Hz	60Hz	Enclosures	Fuel tank (L)	Dimensions l x w x h (m)	Weight (kg)	Fuel tank (L)	50Hz maximum run time (h)	60Hz maximum run time (h)	LWA	dB(A)@1m	dB(A)@7m	dB(A)@7m
<b>K9</b>	<b>K9U</b>	M125	50	1.48x0.76x1.03	390	93	48.9	40.4	83	67	54	64
<b>K12</b>	<b>K12U</b>	M126	50	1.75x0.78x1.23	510	93	36.8	31.7	83	67	54	64
<b>K16</b>	<b>K16U</b>	M126	50	1.75x0.78x1.23	580	93	25,1	20,7	91	74	61	69
<b>K16H</b>	-	M126	50	1.75x0.78x1.23	480	93	25.6	-	95	79	66	-
<b>K21H</b>	-	M126	50	1.75x0.78x1.23	520	93	19	-	96	80	67	-
<b>K22</b>	<b>K20U</b>	M126	50	1.75x0.78x1.23	660	93	26.6	22,5	87	71	58	67
<b>K27</b>	<b>K25U</b>	M126	50	1.75x0.78x1.23	710	93	19.8	16,7	93	77	64	68
<b>K28H</b>	-	M127	100	2.08x0.96x1.42	750	230	30.7	-	100	83	71	-

## SINGLE PHASE SPECIFICATIONS

Generating sets		Standard enclosures				Enclosures with double wall base frame			Sound levels 50 Hz			Sound levels 60 Hz
50Hz	60Hz	Enclosures	Fuel tank (L)	Dimensions l x w x h (m)	Weight (kg)	Fuel tank (L)	50Hz maximum run time (h)	60Hz maximum run time (h)	LWA	dB(A)@1m	dB(A)@7m	dB(A)@7m
-	<b>K9UM</b>	M126	50	1.75x0.78x1.23	500	93	-	40.4	-	-	-	64
<b>K10M</b>	<b>K12UM</b>	M126	50	1.75x0.78x1.23	520	93	36.8	31.7	83	67	54	64
<b>K12M</b>	<b>K16UM</b>	M126	50	1.75x0.78x1.23	610	93	25,1	20,7	91	74	61	69
<b>K17M</b>	<b>K20UM</b>	M126	50	1.75x0.78x1.23	700	93	26.6	22,5	87	71	58	67